



solid solutions to better hardscapes

- Ideal for wet or frozen surfaces
- Extrudes down to 10°F
- Superior Strength
- Suitable for interior/exterior applications
- Advanced formula

ADHESIVE

Highest performing product of its kind

Retaining Wall • Paver • Masonry • Concrete

DANGER:
EXTREMELY FLAMMABLE.
VAPOR HARMFUL.
Read cautions on rear panel.

NET 10 FL. OZ. (296 mL)

SRW® Adhesive is the strongest adhesive of its kind. Professionals depend on it for its superior strength and time-tested performance. It is formulated for retaining walls, pavers, block, masonry, concrete, aluminum, steel and most common landscaping materials.

- Works on wet and frozen materials
- Provides a strong, durable bond
- Exceeds the requirements of the APA AFG-01, ASTM D3498 and ASTM C557
- Interior/Exterior applications
- Will not freeze
- Extrudes well in cold temperatures

DIRECTIONS

1. Surfaces must be clean and free from oil, grease, excessive water, ice or any other material that may interfere with proper adhesion. The use of other chemicals may deter proper adhesion.
2. Cut tip on slant for 1/4" to 3/8" bead. Puncture inner seal with nail or wire and place in cartridge gun.
3. Apply adhesive with caulking gun to one of the surfaces in a continuous bead to ensure complete coverage.
4. Apply no more adhesive than you can cover in 10 minutes.
5. Press surfaces together firmly. For faster curing, lift up top product and immediately reposition. Do not smear adhesive.
6. Vertical or slanted applications require permanent additional support.

CLEANUP: Tools and adhesive may be cleaned with mineral spirits while adhesive is wet. Follow solvent vendor's precautions.

USER TIPS

1. If block, paver, etc. has been tumbled, make sure surface is clean of any dust, dirt or material that may deter proper adhesion.
2. When using on tumbled products or steps, we recommend using a 3/8" bead.
3. Not recommended to apply in temperatures below 10°F.
4. Allow 48 hour cure time and 4-5 days before walking on any steps or heavy traffic areas.
5. If materials have grooves, make sure you have full positive connection of adhesive to both surfaces.
6. Not for continuous submersion or use below the waterline.
7. Not for use on plastic, rubber, or fiberglass materials.

DANGER: EXTREMELY FLAMMABLE. VAPOR HARMFUL. Contains acetone, hexane and toluene. Keep away from heat, sparks and flame. Use only with positive cross-ventilation. Avoid breathing vapors. Do not swallow. Do not allow eye contact or prolonged skin contact. Uncured product can cause eye or skin irritation. Prolonged or repeated overexposure to solvents in uncured product can cause central nervous system, peripheral nervous system, eye, skin, liver, kidney or respiratory system effects. **First Aid:** If dizziness or other adverse effects are experienced, move to fresh air; contact physician if discomfort persists. If eye contact occurs, flush eyes with water for 15 minutes; contact physician immediately. If swallowed, do not induce vomiting; contact physician immediately. Wash skin contact areas with soap and water; contact physician if irritation persists. For additional information, please refer to Material Safety Data Sheet. **KEEP OUT OF REACH OF CHILDREN.**

WARNING: This product contains toluene, a chemical known to the State of California to cause birth defects or other reproductive harm.

IMPORTANT NOTICE: Our recommendations, if any, for the use of this product are based on tests believed to be reliable. Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied, is made for the merchantability, fitness or suitability for the use of this product or otherwise extending beyond the description hereof except the obligation to replace that product for portion of shipment proved defective. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use. Liability is limited to product replacement only.

Calculated VOC: 303 g/L

For product information in Spanish or French, please see your distributor or visit www.srwproducts.com

Do Not Store In Direct Sunlight

Reorder # 56441

Manufactured in the USA for:
SRW Products
www.srwproducts.com
P.O. Box 70 Princeton, MN 55371
1-800-752-9326

