



Woven Ground Cover Fabric

Color Black Scrim with Green Stripe/12"
Basis Weight 3 oz/yd²
Mesh 15 x 10/11

Item	Test Method	MD	CD	Unit
Grab Tensile Strength	ASTM D 4632	155	106	LBS
Grab Tensile Elongation		25%	23%	%
Mullen Bursting Strength	ASTM D 3786	254		PSI
Trapezoidal Tear Strength	ASTM D 4533	109	78	LBS
CBR Puncture Strength	ASTM D 4833	68		LBS
AOS	ASTM D 4751	40		US SIEVE
UV Resistance, % Retained	ASTM D 4355	<70% after 2500 Hrs		
HYDRAULICS (Cross Plane) [Water Head 5cm]				
Water Permittivity	ASTM D 4491	sec ⁻¹		sec ⁻¹
Water Flow Rate		2.79		Gal/ft ² /min

April 2013. This data sheet supersedes all previously issued data sheets. The above properties are typical average based on test data only. The average deviation shall be ± 10% of the above values. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled, however, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information nor do we offer any warranty against patent infringement.