



solid solutions to better hardscapes

PO Box 70 • 32020 126th St • Princeton, MN 55371 • Tel 800-752-9326 • Fax 763-389-2725

Material Safety Data Sheet

SRW Products

Retaining Wall and Paver Adhesive

VOC

1. Product and company identification

Address: SRW Products
32020 126th Street
Princeton, MN 55371

Contact person: SRW Products Technical Services
Telephone: (800) 752-9326
In case of emergency: (800) 424-9300

Product code: 56491

Date of revision: 01-07-2015
Print date: 01-07-2015
Chemtrec (24 Hour): (800) 424 - 9300
Chemtrec International: (703) 527 - 3887

Product use: Construction Adhesive
Proprietary Polymer

2. Hazards identification

Emergency Overview

Physical state: Liquid. [Paste.]
Color: Beige.
Odor: Solvent. [Strong]
Signal word: Danger!

Hazard statements: EXTREMELY FLAMMABLE LIQUID AND VAPOR. FLAMMABLE. VAPOR MAY CAUSE FLASH FIRE. HARMFUL IF INHALED. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. MAY BE HARMFUL IF SWALLOWED. REPRODUCTIVE HAZARD - CONTAINS MATERIAL WHICH CAN CAUSE ADVERSE REPRODUCTIVE EFFECTS IN FEMALES.

Precautionary measures: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Keep container tightly closed. Use personal protective equipment as required. Wash thoroughly after handling.

OSHA/HCS status: This material is considered hazardous by the OSHA Hazard Communication Standard

Routes of entry Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Inhalation: Toxic by inhalation. Irritating to respiratory system.
Ingestion: Harmful if swallowed.
Skin: Irritating to skin.
Eyes: Severely irritating to eyes. Risk of serious damage to eyes.

Potential chronic health effects

Chronic effects: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Carcinogenicity: No known significant effects or critical hazards.

Mutagenicity: No known significant effects or critical hazards.

Teratogenicity: No known significant effects or critical hazards.

Developmental effects: No known significant effects or critical hazards.

Fertility effects: Contains material which can impair female fertility.

Target organs: Contains material which may cause damage to the following organs: blood, kidneys, the nervous system, the reproductive system, liver, peripheral nervous system, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

Over-exposure signs/symptoms

Inhalation: Irritating to respiratory system. High vapor concentrations can cause headaches, dizziness, drowsiness and nausea and may lead to unconsciousness. Adverse symptoms may include the following: respiratory tract irritation, coughing, reduced fetal weight, increase in fetal deaths, skeletal malformations.

Ingestion: Harmful if swallowed.

Skin: Irritating to skin. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Eyes: Irritating to eyes. This product may irritate eyes upon contact.
Watering, redness

See toxicological information (Section 11)

Medical conditions: None known.

Aggravated by overexposure

3. Composition/information on ingredients

| Name | CAS number | % |
|------------------------|------------|-----------|
| methyl acetate | 79-20-9 | 25 - 50 |
| oxydipropyl dibenzoate | 27138-31-4 | 1 - 5 |
| methanol | 67-56-1 | 0.1 - 0.5 |
| vinyl acetate | 108-05-4 | 0.1 - 0.5 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Eye contact: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

Skin contact: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

Inhalation: Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

Ingestion: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Notes to physician: No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

Flammability of the product: Extremely flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

Extinguishing media

Suitable : Use dry chemical, CO₂, water spray (fog) or foam.

Not suitable : Do not use water jet.

Special exposure hazards: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool

Special protective

equipment for fire-fighters: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Small spill: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Absorb with an inert material.

Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7. Handling and storage

Handling: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage: Store between the following temperatures: -17 to 40°C (1.4 to 104°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Methyl Acetate

ACGIH TLV (United States, 3/2012).

TWA: 200 ppm 8 hour(s).

TWA: 606 mg/m³ 8 hour(s).

STEL: 250 ppm 15 minute(s).

STEL: 757 mg/m³ 15 minute(s).

OSHA PEL 1989 (United States, 3/1989).

TWA: 200 ppm 8 hour(s).

TWA: 610 mg/m³ 8 hour(s).

STEL: 250 ppm 15 minute(s).

STEL: 760 mg/m³ 15 minute(s).

NIOSH REL (United States, 6/2009).

TWA: 200 ppm 10 hour(s).

TWA: 610 mg/m³ 10 hour(s).

STEL: 250 ppm 15 minute(s).

STEL: 760 mg/m³ 15 minute(s).

OSHA PEL (United States, 6/2010).

TWA: 200 ppm 8 hour(s).

TWA: 610 mg/m³ 8 hour(s).

Vinyl Acetate

ACGIH TLV (United States, 3/2012).

TWA: 10 ppm 8 hour(s).

TWA: 35 mg/m³ 8 hour(s).

STEL: 15 ppm 15 minute(s).

STEL: 53 mg/m³ 15 minute(s).

OSHA PEL 1989 (United States, 3/1989).

TWA: 10 ppm 8 hour(s).

TWA: 30 mg/m³ 8 hour(s).

STEL: 20 ppm 15 minute(s).

STEL: 60 mg/m³ 15 minute(s).

NIOSH REL (United States, 6/2009).

CEIL: 4 ppm 15 minute(s).

CEIL: 15 mg/m³ 15 minute(s).

Consult local authorities for acceptable exposure limits.

Recommended monitoring

procedures: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Hygiene measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

- Respiratory:** Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Hands :** Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eyes:** Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
- Skin:** Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Environmental exposure

- Controls:** Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

9. Physical and chemical properties

- Physical state:** Liquid. [Paste.]
- Flash point :** Closed cup: -13°C (8.6°F) [Setaflash.]
- Color:** Beige.
- Odor:** Solvent(s) [Strong]
- Boiling/condensation point:** 54.44°C (130°F)
- Relative density:** 1.306
- Volatility:** 30.13% (w/w)
- Evaporation rate:** >1 (butyl acetate = 1)
- VOC (less water, less exempt solvents):** 47g/l
- Solubility:** Insoluble in the following materials: cold water and hot water.

10. Stability and reactivity

- Chemical stability:** The product is stable.
- Conditions to avoid:** Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
- Incompatible materials:** Highly reactive or incompatible with the following materials: oxidizing materials
- Hazardous decomposition Products:** Under normal conditions of storage and use, hazardous decomposition products should not be produced.
- Possibility of hazardous Reactions:** Under normal conditions of storage and use, hazardous reactions will not occur.
- Hazardous polymerization:** Under normal conditions of storage and use, hazardous polymerization will not occur.
- Incompatibility:** Reactive or incompatible with the following materials: oxidizing materials, acids and alkalis.

Conditions of reactivity: Flammable in the presence of the following materials or conditions:
open flames, sparks and static discharge and heat.

11. Toxicological information

United States

Acute toxicity: No known significant effects or critical hazards

Chronic toxicity: No known significant effects or critical hazards

Irritation/Corrosion: Moderate irritant to skin and eyes.

Skin: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Eyes: This product may irritate eyes upon contact

Respiratory: High vapor concentrations can cause headaches, dizziness, drowsiness and nausea and may lead to unconsciousness.

Sensitizer: No known significant effects or critical hazards

Carcinogenicity: Vinyl Acetate- ACGIH, A3- IARC, 2B

Mutagenicity: No known significant effects or critical hazards

Teratogenicity: No known significant effects or critical hazards

Reproductive toxicity: No known significant effects or critical hazards

12. Ecological information

United States

Aquatic ecotoxicity: No known significant effects or critical hazards.

Ecotoxicity : No known significant effects or critical hazards.

13. Disposal considerations

Waste disposal: The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION. for additional handling information and protection of employees.

14. Transport information

DOT Classification: UN number: 1133
Proper Shipping Name: Adhesives, containing flammable liquid
Class: 3
Packing Group: III
Label: Flammable Liquid, 3
Remark: Limited Quantity

15. Regulatory information

HCS Classification: Flammable liquid
Irritating material
Carcinogen

U.S. Federal regulations:

TSCA 8(a) PAIR: methyl acetate; mequinol

TSCA 8(a) IUR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): All components are listed or exempted.

SARA 302/304/311/312 extremely hazardous substances: No products were found.

SARA 302/304 emergency planning and notification: No products were found.

SARA 302/304/311/312 hazardous chemicals: methyl acetate

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Low

VOC Premix: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard; methyl acetate: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard

Clean Air Act Section

112(b) Hazardous Air

Pollutants (HAPs): Not listed

Clean Air Act Section 602

Class I Substances: Not listed

Clean Air Act Section 602

Class II Substances: Not listed

DEA List I Chemicals

(Precursor Chemicals): Not listed

DEA List II Chemicals

(Essential Chemicals): Not listed

State regulations

Massachusetts:

The following components are listed: METHYL ACETATE

New York:

The following components are listed: Vinyl acetate

New Jersey:

The following components are listed: METHYL ACETATE; ACETIC ACID, METHYL ESTER; VINYL ACETATE; ACETIC ACID ETHENYL ESTER

Pennsylvania:

The following components are listed: ACETIC ACID, METHYL ESTER; ACETIC ACID ETHENYL ESTER

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

methanol :

| | |
|-------------------------------|--------------------------|
| Cancer- | No. |
| Reproductive- | Yes. |
| No significant risk level- | 45000 µg/day(ingestion) |
| | 47000 µg/day(inhalation) |
| Max. acceptable dosage level- | No. |

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Chemical Weapons

Convention List Schedule I

Chemicals:

Not listed

Chemical Weapons

Convention List Schedule

II Chemicals:

Not listed

Chemical Weapons

Convention List Schedule

III Chemicals:

Not listed

16. Other information

Label requirements: EXTREMELY FLAMMABLE LIQUID AND VAPOR. FLAMMABLE. VAPOR MAY CAUSE FLASH FIRE. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. MAY BE HARMFUL IF SWALLOWED. POSSIBLE CANCER HAZARD – CONTAINS MATERIAL WHICH MAY CAUSE CANCER.

Hazardous Material

Information System (U.S.A.):

| | |
|------------------|---|
| Health- | 2 |
| Flammability | 3 |
| Physical hazards | 0 |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.